TABLE-TOP BINDER BQ-P65



BINDING BQ-P65

QUALITY BINDING WITH SIMPLE OPERATION.



Scan QR code and watch the product video.



BENEFITS

EASY OPERATION

Simple operation panel with navigation indicator for easy operation.

FLEXIBLE BINDING STYLES

Choose from three different binding styles : Cover Binding, Tape Binding, Pad Binding.





Tape Binding



Cover Binding

Pad Binding

HIGH QUALITY

A cover is glued to the book spine and then clamped to create a quality bound book.

The BQ-P65 applies a thinner glue film on the spine for higher quality padding.

OFFICE FRIENDLY OPERATION

An integrated odor extractor and filter system is a standard feature to clean the air and remove any glue odors from office environments.

ENERGY SAVING

Low-temperature glue and power saving mode to reduce energy consumption.

PERFECT FOR BINDING MANUALS AND DOCUMENTS IN-HOUSE.

CLAMPING SECTION

The book block is firmly clamped, to produce a professional quality book up to 25 mm (0.98") thickness.

NIPPING SECTION

Nipping strength is adjusted automatically according to the binding style for a higher quality finish.





COVER SECTION

Cover and tape can be applied to the spine. Tape widths of 30 mm to 40 mm (1.2" to 1.6") can be used.

EASY OPERATION





Choose the binding style and insert the book block.

CONSUMABLES.

HM-302 GLUE

ODOR ELIMINATING FILTER

AIR FILTER

PRINTABLE SPINE TAPE

COLORED COVERS

- A4 / B5 size each 5 colors
- Cover for Laser Printer A4 size 2 colors

*The machine design and specifications are subject to change without notice. *Specifications may vary depending on the job, paper quality, environmental influences, and various other factors. Please do a test run before starting production.



Insert a cover (or tape), then press the start button.

SPECIFICATIONS.

4

GLUING SECTION

simple adjustment. Fume extractor

removes glue odors for comfortable

Amount of glue

can be adjusted

depending on the thickness of

the book with

operation.

step.

OPERATION PANEL

Simple operation panel

guides you through the

binding process step by

The book is finished.

BQ-P65		
Binding Type	Cover Binding / Tape Binding / Pad Binding	
Glue Type	Hot melt	
Book Block Size	Foreedge	Spine Length x Fore-edge Length Max. 315 x 210 mm or 12.4" x 8.2" Min. 210 x 148 mm or 8.3" x 5.9"
Book Block Thickness	Max. 25mm or 0.98"	
Cover Size	Width	Length × Width Max. 315 x 445 mm or 12.4" x 17.5" Min. 210 x 297 mm or 8.27" x 11.70"
Cover Weight Range	82 to 210 gsm, 22 to 60 lb	
Glue Temperature	130 to 150 degrees Celsius (266 to 302 degrees Fahrenheit)	
Cycle Speed	22 seconds per cycle (Cover Binding)	
Voltage / Frequency	Single Phase 115 V, 50 or 60 Hz Single Phase 220 to 240 V, 50 or 60 Hz	
Rated Current	Single Phase 115 V, 50 or 60 Hz, 10 A Single Phase 220 to 240 V, 50 or 60 Hz, 5 A	
Machine Dimensions	W600 x D615 x H270 mm or 23.7" x 24.3" x 10.7"	
Machine Weight	48 kg or 106 lbs.	



Horizon International Inc.

1601 Asahi, Shinasahicho, Takashima, Shiga, 520-1501, Japan Phone : +81-740-25-4570 Fax : +81-740-25-5820 www.horizon.co.jp

Horizon GmbH

Pascalstrasse 20 25451 Quickborn / Germany Phone : +49 4106 8042-0 Fax : +49 4106 8042-199 www.horizon.de



